



By reducing the amount of friction created during a wire pull, SuperSlick Elite® can increase your ability to maintain a productive, safe and cost-effective job site. SuperSlick Elite features a slick but never slippery or greasy outer jacket for easy pulling without additional lubricant.

Our new formula is tougher and faster to pull

Sunlight-resistant in all colors and in sizes 18 AWG through 1000 KCMIL

SUPERSLICK ELITE®

Slick without the grease and mess, our SuperSlick Elite won't leave residue or disappointment on your next wire pull

SuperSlick Elite Limited Warranty

Encore guarantees that our SuperSlick Elite brand of cables may be installed without the need for additional lubricant to ease the pulling of cables through PVC or metal conduit.

For more information on our warranty, please scan QR code to the right.



SUPERSLICK ELITE, YOUR FORMULA FOR EFFICIENCY AND SUCCESS!



SuperSlick Elite products are available in all colors and sizes to simplify complex wiring jobs, eliminate phase tape and save you time & money.



SuperSlick Elite, as with all of our products, is backed by our industry-leading warranty and unmatched fill-rates.



“ In today's competitive markets, there are few remaining ways for us to separate ourselves from the other contractors. One being the cut to the amount of labor involved in completing the projects we are awarded. This not only adds back into our bottom dollar, but also shows our customer base that we are able to get our projects done efficiently and on time. ”

Nick Johnson, Ault Electric



1.800.962.9473 | encorewire.com

THHN/THWN-2 SUPERSLICK ELITE®	Copper				Aluminum			
	Size (AWG or KCMIL)	PVC Insulation Thickness (in)	Nylon Jacket Thickness (in)	Outside Diameter (in)	Size (AWG or KCMIL)	PVC Insulation Thickness (in)	Nylon Jacket Thickness (in)	Outside Diameter (in)
	18*	0.015	0.004	0.088	18	--	--	--
	16*	0.015	0.004	0.101	16	--	--	--
	14	0.015	0.004	0.109	14	--	--	--
	12	0.015	0.004	0.127	12	--	--	--
	10	0.020	0.004	0.160	10	--	--	--
	8	0.030	0.005	0.212	8	0.030	0.005	0.204
	6	0.030	0.005	0.248	6	0.030	0.005	0.239
	4	0.040	0.006	0.317	4	0.040	0.006	0.305
	3	0.040	0.006	0.344	3	0.040	0.006	0.330
	2	0.040	0.006	0.375	2	0.040	0.006	0.360
	1	0.050	0.007	0.435	1	0.050	0.007	0.413
	1/0	0.050	0.007	0.474	1/0	0.050	0.007	0.450
	2/0	0.050	0.007	0.518	2/0	0.050	0.007	0.490
	3/0	0.050	0.007	0.568	3/0	0.050	0.007	0.537
	4/0	0.050	0.007	0.624	4/0	0.050	0.007	0.589
	250	0.060	0.008	0.678	250	0.060	0.008	0.656
	300	0.060	0.008	0.730	300	0.060	0.008	0.706
	350	0.060	0.008	0.777	350	0.060	0.008	0.752
	400	0.060	0.008	0.821	400	0.060	0.008	0.795
	500	0.060	0.008	0.902	500	0.060	0.008	0.872
	600	0.070	0.009	1.051	600	0.070	0.009	0.971
	700	--	--	--	700	0.070	0.009	1.035
	750	0.070	0.009	1.156	750	0.070	0.009	1.066
	900	--	--	--	900	0.070	0.009	1.157
	1000	0.070	0.009	1.310	1000	0.070	0.009	1.220

* Available only in TFN/TFN SuperSlick Elite copper conductors.

XHHW-2 SUPERSLICK ELITE®	Copper			Aluminum		
	Size (AWG or KCMIL)	XLPE Insulation Thickness (in)	Outside Diameter (in)	Size (AWG or KCMIL)	XLPE Insulation Thickness (in)	Outside Diameter (in)
	14	0.030	0.131	14	--	--
	12	0.030	0.149	12	--	--
	10	0.030	0.173	10	--	--
	8	0.045	0.236	8	0.045	0.224
	6	0.045	0.274	6	0.045	0.259
	4	0.045	0.322	4	0.045	0.303
	3	0.045	0.350	3	0.045	0.328
	2	0.045	0.382	2	0.045	0.358
	1	0.055	0.438	1	0.055	0.409
	1/0	0.055	0.470	1/0	0.055	0.446
	2/0	0.055	0.514	2/0	0.055	0.486
	3/0	0.055	0.564	3/0	0.055	0.533
	4/0	0.055	0.620	4/0	0.055	0.585
	250	0.065	0.671	250	0.065	0.650
	300	0.065	0.724	300	0.065	0.700
	350	0.065	0.771	350	0.065	0.746
	400	0.065	0.815	400	0.065	0.789
	500	0.065	0.896	500	0.065	0.866
	600	0.080	1.023	600	0.080	0.973
	700	--	--	700	0.080	1.037
	750	0.080	1.158	750	0.080	1.068
	900	--	--	900	0.080	1.159
	1000	0.080	1.312	1000	0.080	1.220

