



By reducing the amount of friction created during a wire pull, SuperSlick Elite® can increase your ability to maintain a productive, safe and cost-effective job site. SuperSlick Elite features a slick but never slippery or greasy outer jacket for easy pulling without additional lubricant.

Our new formula is tougher and faster to pull

Sunlight-resistant in all colors and in sizes 18 AWG through 1000 KCMIL

SUPERSLICK ELITE®

Slick without the grease and mess, our SuperSlick Elite® won't leave residue or disappointment on your next wire pull

SuperSlick Elite Limited Warranty

Encore guarantees that our SuperSlick Elite® brand of cables may be installed without the need for additional lubricant to ease the pulling of cables through PVC or metal conduit.

For more information on our warranty, please scan QR code to the right.



SUPERSLICK ELITE, YOUR FORMULA FOR EFFICIENCY AND SUCCESS!



SuperSlick Elite® products are available in all colors and sizes to simplify complex wiring jobs, eliminate phase tape and save you time & money.



SuperSlick Elite®, as with all of our products, is backed by our industry-leading warranty and unmatched fill-rates.



“ In today's competitive markets, there are few remaining ways for us to separate ourselves from the other contractors. One being the cut to the amount of labor involved in completing the projects we are awarded. This not only adds back into our bottom dollar, but also shows our customer base that we are able to get our projects done efficiently and on time. ”

Nick Johnson, Ault Electric



1.800.962.9473 | encorewire.com

THHN/THWN-2 SUPERSLICK ELITE®	Copper				Aluminum			
	Size (AWG or KCMIL)	PVC Insulation Thickness (in)	Nylon Jacket Thickness (in)	Outside Diameter (in)	Size (AWG or KCMIL)	PVC Insulation Thickness (in)	Nylon Jacket Thickness (in)	Outside Diameter (in)
14	0.015	0.004	0.109	14	--	--	--	
12	0.015	0.004	0.128	12	--	--	--	
10	0.020	0.004	0.161	10	--	--	--	
8	0.030	0.005	0.213	8	0.030	0.005	0.204	
6	0.030	0.005	0.249	6	0.030	0.005	0.239	
4	0.040	0.006	0.318	4	0.040	0.006	0.305	
3	0.040	0.006	0.346	3	0.040	0.006	0.330	
2	0.040	0.006	0.378	2	0.040	0.006	0.360	
1	0.050	0.007	0.435	1	0.050	0.007	0.413	
1/0	0.050	0.007	0.474	1/0	0.050	0.007	0.450	
2/0	0.050	0.007	0.518	2/0	0.050	0.007	0.490	
3/0	0.050	0.007	0.568	3/0	0.050	0.007	0.537	
4/0	0.050	0.007	0.624	4/0	0.050	0.007	0.589	
250	0.060	0.008	0.678	250	0.060	0.008	0.656	
300	0.060	0.008	0.730	300	0.060	0.008	0.706	
350	0.060	0.008	0.777	350	0.060	0.008	0.752	
400	0.060	0.008	0.821	400	0.060	0.008	0.795	
500	0.060	0.008	0.902	500	0.060	0.008	0.872	
600	0.070	0.009	1.051	600	0.070	0.009	0.971	
700	--	--	--	700	0.070	0.009	1.035	
750	0.070	0.009	1.156	750	0.070	0.009	1.066	
900	--	--	--	900	0.070	0.009	1.157	
1000	0.070	0.009	1.310	1000	0.070	0.009	1.220	

XHHW-2 SUPERSLICK ELITE®	Copper			Aluminum		
	Size (AWG or KCMIL)	XLPE Insulation Thickness (in)	Outside Diameter (in)	Size (AWG or KCMIL)	XLPE Insulation Thickness (in)	Outside Diameter (in)
14	0.030	0.131	14	--	--	
12	0.030	0.150	12	--	--	
10	0.030	0.173	10	--	--	
8	0.045	0.236	8	0.045	0.224	
6	0.045	0.274	6	0.045	0.259	
4	0.045	0.322	4	0.045	0.303	
3	0.045	0.350	3	0.045	0.328	
2	0.045	0.382	2	0.045	0.358	
1	0.055	0.431	1	0.055	0.409	
1/0	0.055	0.470	1/0	0.055	0.446	
2/0	0.055	0.514	2/0	0.055	0.486	
3/0	0.055	0.564	3/0	0.055	0.533	
4/0	0.055	0.620	4/0	0.055	0.585	
250	0.065	0.672	250	0.065	0.650	
300	0.065	0.724	300	0.065	0.700	
350	0.065	0.771	350	0.065	0.746	
400	0.065	0.815	400	0.065	0.789	
500	0.065	0.896	500	0.065	0.866	
600	0.080	1.053	600	0.080	0.973	
700	--	--	700	0.080	1.037	
750	0.080	1.158	750	0.080	1.068	
900	--	--	900	0.080	1.159	
1000	0.080	1.312	1000	0.080	1.220	

