

TYPE MC HCF-SG (SMARTGROUND™) - COPPER CONDUCTOR - STEEL ARMOR - 600V THHN/THWN-2 INNERS

ENGINEERING SPECIFICATIONS

Standards

Underwriters Laboratories Standards UL-83, UL-1569, UL-1581, UL-2556 for type MC; Federal Specification A-A59544; NEMA RV 1-2014, NEMA WC70/CEA S-95-658; IEEE 1202 (70,000 Btu/hr) Vertical Cable Tray Flame Test; NFPA 70 (NEC®) Article 330; ARRA 2009 Section 1605 "Buy American" Compliant; RoHS Compliant; MasterSpec Division 26 Sections 260519, 260523; UL Listing #E-301130



SMARTCOLORID
HCF-SG™

APPLICATIONS

Type MC cable shall be permitted as follows:

- Suitable for applications requiring branch circuits for non-essential, general purposes electrical systems in patient care areas/spaces of health care facilities per NEC 517.13(a) and (b) or for use in essential electrical systems when in accordance with NEC 517.30(C)(3)(3);
- Acceptable in facilities such as hospitals, nursing homes, dental offices, and other types of medical facilities including out-patient facilities;
- Permitted use for branch circuits in industrial, commercial, and multi-residential buildings;
- Acceptable for power, lighting, control, and signal circuits;
- Allowable in concealed or exposed systems;
- Permitted use in dry locations and embedded in plaster finish on brick or other masonry except in damp or wet locations;
- Utilized for environmental air-handling spaces (NEC 300.22(C)(1));
- Allowable in assembly occupancies (NEC 518.4);
- Permissible in theaters, audience areas of motion pictures, television studios, and similar locations (NEC 520.5);
- Allowable installations in approved raceways and cable trays (NEC 392);
- Suitable for installation under raised floors for IT equipment (NEC 645.5(E));
- Permitted in Class I Div. 2, Class II Div. 2, and Class III Div. 1 Hazardous Locations;
- Listed for use with UL 1479 - 1, 2, and 3 Hour Through-Penetration Firestop Systems.

CONSTRUCTION

Available in sizes 12 AWG through 10 AWG. Encore's Metal-Clad Cable is constructed with soft-drawn copper, Type THHN/THWN-2 conductors rated 90°C dry. All conductors are individually wrapped with flame retardant colored protective paper with print legend and cabled together to form the cable core. Includes green ground same size as circuit conductors. The bare aluminum grounding/bonding conductor is located outside the paper wrap and is cabled with the insulated conductors and in constant contact with sheathing per NEC 250.118(10)(b). Interlocked galvanized lightweight steel armor is applied over the entire assembly.



- 1 Removable SmartColorID® Label
- 2 Interlocked Galvanized Lightweight Steel Armor
- 3 Colored Flame-Retardant Protective Paper Covering
- 4 Aluminum Ground/Bond Wire
- 5 PVC Insulation with Nylon Jacket
- 6 THHN/THWN-2 Solid Copper

Conductors			Green THHN Copper Ground (AWG)	Outside Diameter Over Armor (in)	Total Weight of Type MC-Copper Conductor (lbs/1000 ft)	Allowable Ampacity (Amps) ²			Standard Packaging (ft)	
AWG/No.	Type	Grounding/Bonding Wire				60°C	75°C	90°C	Coils	Reels
12/2	Solid	10 Solid AL	12	0.490	171	20	25	30	250'	1000'
12/3	Solid	10 Solid AL	12	0.503	202	20	25	30	250'	1000'
12/4	Solid	10 Solid AL	12	0.538	232	20	25	30	250'	1000'
10/2	Solid	8 Solid AL	10	0.544	234	30	35	40	250'	1000'
10/3	Solid	8 Solid AL	10	0.587	280	30	35	40	250'	1000'
10/4	Solid	8 Solid AL	10	0.632	327	30	35	40	250'	1000'

¹ SmartColorID manufactured under Patent No. 7,954,530, 8,454,785, 8,826,960 & 8,905,108

² Ampacity of conductors are based on NFPA 70 (NEC) Table 310.15(B)(16). See 110.14(C), 240.4(D) and 310.15(B) for other limitations where applicable.

For equipment marked for use at higher temperatures, the conductor ampacity shall be limited to the following per NEC 110.14(C):

60°C when terminated to equipment for circuits rated 100 amperes or less or marked for size 14 AWG through 1 AWG conductor.

75°C when terminated to equipment for circuits rated over 100 amperes or marked for conductors larger than 1 AWG.

90°C for ampacity derating purposes.

When the neutral is considered current-carrying conductor, the ampacity of 4/C cables shall be reduced by a factor of 0.80 per NEC 310.15(B)(3)(a).

The above data is approximate and subject to normal manufacturing tolerances.

FEATURES

The NEC 250.118(10)(b) recognizes the combination of interlocking armor and bond wire as an equipment grounding conductor. The green insulated copper equipment grounding conductor sized per NEC 517.13(B) and 250.122. Insulating anti-short bushings are supplied with each reel or coil, but not required per Section 330.40 of the NEC. Suitable for type MCI-A fittings. SmartColorID labels are spaced at regular intervals on the exterior of the metal sheathing and are removable. For ease of installation and pulling, cable is reverse wound on reels. Coils are designed to be pulled from the inside.

Standard Conductor Color Coding

No.	120V/208V/240V	No.	277V/480V
2	Black/White	2	Brown/Gray
3	Black/Red/White	3	Brown/Orange/Gray
4	Black/Red/Blue/White	4	Brown/Orange/Yellow/Gray
Ground	Green	Ground	Green

Additional colors available subject to ERQ

SmartColorID Legend:

