

Type EF Flexible Conduit

This non-UL flexible liquid-tight conduit conforms to the JIC standards for dimensions and general construction.

CONSTRUCTION:

The flexible inner core is constructed from a helically formed strip of corrosion-resistant steel. A liquid-tight PVC jacket is then extruded over the core.

APPLICATIONS:

Type EF is used for general installations requiring some movement and protection for contained conductors. Forms a liquid-tight system when installed with standard connectors for use indoors or outdoors.

STANDARD COLORS:

Machine Tool Gray. Other colors available upon request

WORKING TEMPERATURES:

-20°C to 80°C

METAL USED:

Steel

PLASTIC USED:

PVC



Type EF Flexible Conduit

Trade Size (in)	Type	Inside Bend Radius (in)	Weight (lbs/100ft)	Standard Packaging	
				Carton (ft)	Reel (ft)
3/8"	EF-10	1.5	20	100', 500'	1000'
1/2"	EF-11	2.0	24	100', 500'	1000'
3/4"	EF-12	2.5	31	100', 500'	1000'
1"	EF-13	3.0	43	100', 400'	-
1 1/4"	EF-14	3.5	60	50', 200'	-
1 1/2"	EF-15	4.5	78	50', 150'	-
2"	EF-16	5.5	104	50', 100'	-

